

PFISTERER



EHV cable accessories

The complete range for all 420 kV high-voltage cables

www.pfisterer.com

The complete range for all 420 kV high-voltage cables

The new range of high-voltage cable accessories includes dry, pluggable cable connections for transformers and GIS, cable terminations, cable joints and pluggable cable joints. The type-tested accessories can be used for all XLPE cables and are adapted individually to the cable used. Therefore, for the first time ever, cable lengths can be constructed with accessories from a single source. The field control units under high load during operation are individually tested before delivery according to IEC 62067. This ensures the highest operational safety for decades.

EHV-CONNEX dry, pluggable cable connector



In the EHV version, the type tested connector system for XLPE cables contains copper or aluminum cables with conductor cross sections up to 3,000 mm². An integrated cable bracing system reliably protects the contact system from mechanical load through the cable and simplifies the cable management.

- Nominal current up to $I_N = 4,000$ A
- Maximum operating voltage $U_m = 420$ kV
- Cu or Al cable up to 3,000 mm²
- Diameter over insulation: 144 mm
- Tested according to IEC 62067
- Touch proof, waterproof and maintenance-free
- Suitable for offshore use, salt-water resistant

EHV-CONNEX socket for transformers and GIS



The EHV version of the CONNEX sockets offer all advantages of the CONNEX system. There are designs for transformers in accordance with EN 50299 and IEC 62271-209 for GIS. If the terminal compartment does not need to be designed according to the standard, the standard design for the sockets allows for an extremely compact construction.

- Nominal current up to $I_N = 4,000$ A
- Maximum operating voltage $U_m = 420$ kV
- Tested according to IEC 62067
- No gas or oil work during installation
- More compact than conventional systems in accordance with EN 50299/IEC 62271-209

IXOSIL ESS 420 cable termination



The supporting cable terminations, ESS model, offer the highest mechanical stability due to the fiber glass reinforced hollow insulator with a water-repellent shield made of silicon. A porcelain version is also available on request. The head armature is equipped with patented SICON bolted technique. These bolts allow the most varied conductor cable cross sections to be connected with the optimum contact force and without special tools.

- Maximum nominal current limited only through the high-voltage cable
- Maximum operating voltage $U_m = 420$ kV
- Cu or Al cable up to $2,500$ mm²
- Tested according to IEC 62067
- Pollution class (65 mm/kV) according to IEC 60815
- Highest mechanical stability thanks to the fiber glass reinforced hollow insulator
- Silicon shielding for ideal water-repellent behavior
- Simple assembly of the head armature
- Maintenance free

IXOSIL MSA 420 slip-on joint



The time tested interface technology of the IXOSIL joints ensure simple installation of the waterproof, external housing and maximum operational safety. Using the patented SICON bolted connector connections allows the conductor to be connected with optimal contact force and without special tools. The cable shielding is adapted individually for cable type and customer needs.

- Maximum nominal current limited only through the high-voltage cable
- Maximum operating voltage $U_m = 420$ kV
- Cu or Al cable up to $2,500$ mm²
- Tested according to IEC 62067

EHV-CONNEX dry, pluggable, gas-insulated joint



Cables of the most varied designs and sizes can be connected stably using the pluggable cable sockets. Furthermore, they are also used for testing devices and cable systems for separable connection to the high voltage.

- Connection of the most varied cable cross sections and cable types
- Nominal current up to $I_N = 4,000$ A
- Maximum operating voltage $U_m = 420$ kV
- Cu or Al cable up to $3,000$ mm²
- Tested according to IEC 62067
- Compact construction for space-saving connections
- Pre-tested in the factory
- SF₆ gas insulation with integrated fill-pressure monitoring

EHV accessories from experts

PFISTERER is an independent manufacturer of cable accessories for all types of medium and high-voltage cables. In addition to cable accessories, the world's broadest product range also offers comprehensive solutions for special applications, as well as a full range of installation and testing accessories. Experienced experts teach the installation of the accessories at the company's training center or directly at the customer site. In addition, the worldwide cable installations, project planning and turn-key creation of complete cable systems also belong to the scope of service.

PFISTERER Kontaktsysteme GmbH
Rosenstraße 44
73650 Winterbach
Germany
Tel: +49 7181 7005 0
Fax: +49 7181 7005 565
ehv@pfisterer.com
www.pfisterer.com

PFISTERER | IXOSIL AG
Gotthardstrasse 31
6460 Altdorf
Switzerland
Tel: +41 41 874 75 75
Fax: +41 41 874 75 76
ehv@pfisterer.com
www.ixosil.ch